



## 4G LTE

### Cellular Communicators

Honeywell Home is focused on providing the best alarm communication solutions for the security industry. Alternative communication methods are critical in the marketplace due to VoIP, migration from POTS and the evolution of cellular networks. LTE network connectivity provides the longest viable cellular lifespan available.

All signals are delivered to the Honeywell Home AlarmNet® Network Control Center, which routes the information to the appropriate central station. The state-of-the-art AlarmNet Network Control Center is fully redundant and monitored 24/7. AlarmNet has the ability to route messages using AlarmNet-i and 800 PLUS services, providing true redundancy and multi-path message delivery.

### Honeywell Home End-to-End Solutions



## FEATURES

- **4G LTE network compatibility**
- **Full Contact ID**  
Contact ID reporting using ECP mode with compatible Honeywell Home control panels.
- **256-bit AES Encryption**  
Advanced encryption standard used for secure communications.
- **Upload/Download**  
Available with select Honeywell Home control panels. Requires Compass version 1.5.8.54a or higher.
- **Integration**  
Quick and easy installation of cellular communicator for VISTA® and LYNX controls.
- **Diagnostic LEDs**  
Provide signal strength and status indications.
- **QOS**  
Quality of Service diagnostics via AlarmNet supply vital information including when a message was received, battery voltage, input voltage, signal strength and message path.
- **AlarmNet360™ Online Management Platform**  
AlarmNet360 Account Management [www.alarmnet360.com/](http://www.alarmnet360.com/) — Remote programming and diagnostics to improve business efficiencies and reduce truck rolls.
- **Remote Services Capability\***  
Optional Honeywell Total Connect Remote Services — Boost RMR while providing on-the-go security and home control, video viewing, and real-time alerts, anytime, anywhere, on any PC or smart device.
- **Two-way Voice Transport**  
Capable of allowing two-way voice session in conjunction with VoLTE (LYNX and LYRIC models only) an audio verification system (U.S. and Canada only).
- **FOTA Firmware Upgrading**  
Complete over-the-air firmware upgrading capability. Provides remote service management ability.

\*Service subscription required.

# SPECIFICATIONS

## VISTA 4G LTE Communicators (LTE-XV/LTE-XA/LTE-XC)



<b>DESCRIPTION</b>	<ul style="list-style-type: none"> <li>• Integrated VISTA ECP design</li> <li>• Four-wire connection</li> <li>• Powered by VISTA</li> <li>• LTE CAT 1</li> </ul>
<b>PANEL COMPATIBILITY</b>	All VISTA controls with ECP radio support
<b>DIMENSIONS</b>	8.4" x 8.0" x 1.5" (21.3cm x 20.3cm x 3.8cm)
<b>ELECTRICAL</b>	<b>Input Power:</b> powered from 12V aux power <b>Current Drain:</b> 210mV
<b>RF</b>	<b>Antenna:</b> Internal Penta-Band antenna with receive diversity.
<b>ENVIRONMENTAL</b>	<b>Operating Temperature:</b> -4° to 131° F (-20° to 55° C) <b>Storage Temperature:</b> -40° to 158° F (-40° to 70° C)
<b>AGENCY LISTINGS</b>	ETL Listed

## LYRIC 4G LTE Communicators (LYRICLTE-A/LYRICLTE-C/LYRICLTE-V)



<b>DESCRIPTION</b>	LYRICLTE-A: LTE CAT 3 LYRICLTE-V: LTE CAT 1
<b>PANEL COMPATIBILITY</b>	Lyric Controller firmware version 1.09 or greater Lyric Gateway firmware version 1.02 or greater (LTE-A only) Lyric Controller Canada (LTE-C) firmware version 1.07 or greater
<b>DIMENSIONS</b>	3.15" x 2.44" x 0.55" (80cm x 62cm x 14cm)
<b>ELECTRICAL</b>	<b>Input Power:</b> 7.2V <b>Current Drain:</b> 245mA
<b>RF</b>	<b>Antenna:</b> Integrated LDS Penta-Band antennas with receive diversity.
<b>ENVIRONMENTAL</b>	<b>Operating Temperature:</b> -4° to 131° F (-20° to 55° C) <b>Storage Temperature:</b> -40° to 158° F (-40° to 70° C)
<b>AGENCY LISTINGS</b>	ETL listed

# SPECIFICATIONS

## LYNX Touch 4G LTE Communicators (LTE-L57V/LTE-L57A/ LTE-L57C)



<b>DESCRIPTION</b>	Integrated Volte-capable LTE CAT1 cellular communicator for LYNX Touch
<b>PANEL COMPATIBILITY</b>	L5210/L7000 controls version 9.00.xxx
<b>DIMENSIONS</b>	4.75" x 2.5" (12.1cm x 6.4cm)
<b>ELECTRICAL</b>	<b>Input Power:</b> 5V <b>Current Drain:</b> 490mA
<b>RF</b>	<b>Antenna:</b> Internal Penta-Band antenna with receive diversity.
<b>ENVIRONMENTAL</b>	<b>Operating Temperature:</b> -4° to 131° F (-20° to 55° C) <b>Storage Temperature:</b> -40° to 158° F (-40° to 70° C)
<b>AGENCY LISTINGS</b>	ETL Listed

## L3000 4G LTE Communicators (LTE-L3A/ LTE-L3V)



<b>DESCRIPTION</b>	Integrated VoLTE capable LTE CAT1 cellular communicator for LYNX Plus
<b>PANEL COMPATIBILITY</b>	<ul style="list-style-type: none"> <li>• LYNX Plus Controls</li> <li>• L3000 Series</li> </ul>
<b>DIMENSIONS</b>	5.25" x 2.25" (13.3cm x 5.7cm)
<b>ELECTRICAL</b>	<b>Input Power:</b> 8VDC <b>Current Drain:</b> 315mA
<b>RF</b>	<b>Antenna:</b> Internal Octa-Band antenna with receive diversity.
<b>ENVIRONMENTAL</b>	<b>Operating Temperature:</b> -4° to 131° F (-20° to 55° C) <b>Storage Temperature:</b> -40° to 158° F (-40° to 70° C)
<b>AGENCY LISTINGS</b>	Listings pending

# ORDERING

## U.S.

LTE SKU	Carrier	Panel Compatibility	Replaced 3G/4G CDMA Radio
LYRICLTE-A	AT&T	LCP500-L LCP300-L	LYRIC-3G/LYRIC-CDMA
LYRICLTE-V	Verizon	LCP500-L	LYRIC-3G/LYRIC-CDMA
LTE-XV	Verizon	VISTA-15P VISTA-20P VISTA-128BPT VISTA-250BPT	GSMX4G/CDMA-X
LTE-L57V	Verizon	L5210 L7000	3GL/CDMA-L57
LTE-L3V	Verizon	L3000	GSMVLP4G/CDMA-L3
LTE-L3A	AT&T	L3000	GSMVLP4G/CDMA-L3
LTE-XA	AT&T	VISTA-15P VISTA-20P VISTA-128BPT VISTA-250BPT	GSMX4G/CDMA-X
LTE-L57A	AT&T	L5210 L7000	3GL/CDMA-L57

## Canada

LTE SKU	Carrier	Panel Compatibility	Replaced 3G/4G Radio
LYRICLTE-C	Bell	LCP500-LC LCP300-LC	LYRIC - 3GC
LTE-XC	Bell	VISTA-15PCN VISTA-20PCN VISTA-128BPTCN VISTA-250BPTCN	GSMXCN4G
LTE-L57C	Bell	L5210-CN L7000-CN	3GLC
LTE-L3A	AT&T	L3000-CN	GSMVLP4G



### Resideo Technologies, Inc.

2 Corporate Center Drive Suite 100  
P.O. Box 9040  
Melville, NY 11747  
1-800-645-7492  
resideo.com

L/LTEFAMD/D | 07/19  
© 2019 Resideo Technologies, Inc.  
This product is manufactured  
by Resideo and its affiliates. The  
Honeywell Home trademark is  
used under license from Honeywell  
International Inc. All rights reserved.

