



Lyric™ Communicators



The Lyric Controller offers a choice of two of today's most reliable wireless communication technologies. It can use either CDMA (Verizon) or GSM (AT&T and Rogers) communicators. Lyric communicators are designed to be user replaceable—eliminating the need for a service call and improving operational efficiency.



FEATURES

Easier to Sell

A choice of CDMA (Verizon®) or 3G GSM (AT&T®/Rogers™) cellular radios provide you with the flexibility you need to reach more customers.

Easier to Maintain

User-replaceable cellular radios make systems easier to maintain—reducing the need for truck rolls and improving efficiency.

Diagnostic LEDs provide signal strength and status indications.

Remote Services-Ready

Lyric communicators support Resideo Total Connect Remote Services*—boosting your RMR while providing consumers with on-the-go security and home control, video viewing and real-time alerts anytime, anywhere, on any PC or smart device.

Easier to Install

Control panel data can be uploaded and downloaded via CDMA or GSM, simplifying installations.

Secure Encryption

Lyric communicators employ true, 128-bit AES encryption for a high level of security.

*Service subscription required.

Lyric Communicators

FEATURES AND SPECIFICATIONS



Lyric-CDMA*

Digital cellular communicator
for use with Lyric Controller

*Lyric-CDMA available in United States only.

Dimensions:

3.15" H x 2.44" W x 0.55" D (80mm H x 62mm W x 14mm D)

Electrical

- Powered and battery backed directly from Lyric Controller
- Input Voltage: 5VDC nominal
- Quiescent Current: 15mA
- Average Current During Transmit: 300mA

Antenna

- Dual Band: CDMA 1xRTT (800, 1900 MHz)
- VSWR: 3:1
- Peak Gain: 2 dBi
- Impedance: 50 ohms
- Polarization: linear



Lyric-3G/Lyric-3GC

Digital cellular communicator
for use with Lyric Controller

Dimensions:

3.15" H x 2.44" W x 0.55" D (80mm H x 62mm W x 14mm D)

Electrical

- Powered and battery backed directly from Lyric Controller
- Input Voltage: 5VDC nominal
- Quiescent Current: 15mA
- Average Current During Transmit: 300mA

Antenna

- Dual Band: UMTS/HSPA (850, 1900 MHz)
- VSWR: 3:1
- Peak Gain: 3 dBi
- Impedance: 50 ohms
- Polarization: linear

ORDERING

LYRIC-CDMA	Digital Cellular Communicator (Verizon)
LYRIC-3G	Digital Cellular Communicator (AT&T)
Lyric-3GC	Digital Cellular Communicator – Canada Only (Rogers)



Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100
P.O. Box 9040
Melville, NY 11747
1-800-645-7492
resideo.com

For more information

security.honeywellhome.com/hsc

All trademarks are property
of their respective owners.

L/LRCRADD/D | 06/19
© 2019 Resideo Technologies, Inc.
This product is manufactured
by Resideo and its affiliates. The
Honeywell Home trademark is
used under license from Honeywell
International Inc. All rights reserved.

Honeywell Home